

Time spent:
Oct 1, 2, 19, 20.

- Wire:
 21, 22 cl. 24
 23-18, 23-
 24-25, 24-26
 25-27, 25-28
 26-29, 26-30
 27-31, 27-32
 28-33, 28-34
 29-35, 29-36
 30-37, 30-38
 31-39, 31-40
 32-41, 32-42
 33-43, 33-44
 34-45, 34-46
 35-47, 35-48
 36-49, 36-50
 37-51, 37-52
 38-53, 38-54
 39-55, 39-56
 40-57, 40-58
 41-59, 41-60
 42-61, 42-62
 43-63, 43-64
 44-65, 44-66
 45-67, 45-68
 46-69, 46-70
 47-71, 47-72
 48-73, 48-74
 49-75, 49-76
 50-77, 50-78
 51-79, 51-80
 52-81, 52-82
 53-83, 53-84
 54-85, 54-86
 55-87, 55-88
 56-89, 56-90
 57-91, 57-92
 58-93, 58-94
 59-95, 59-96
 60-97, 60-98
 61-99, 61-100
 62-101, 62-102
 63-103, 63-104
 64-105, 64-106
 65-107, 65-108
 66-109, 66-110
 67-111, 67-112
 68-113, 68-114
 69-115, 69-116
 70-117, 70-118
 71-119, 71-120
 72-121, 72-122
 73-123, 73-124
 74-125, 74-126
 75-127, 75-128
 76-129, 76-130
 77-131, 77-132
 78-133, 78-134
 79-135, 79-136
 80-137, 80-138
 81-139, 81-140
 82-141, 82-142
 83-143, 83-144
 84-145, 84-146
 85-147, 85-148
 86-149, 86-150
 87-151, 87-152
 88-153, 88-154
 89-155, 89-156
 90-157, 90-158
 91-159, 91-160
 92-161, 92-162
 93-163, 93-164
 94-165, 94-166
 95-167, 95-168
 96-169, 96-170
 97-171, 97-172
 98-173, 98-174
 99-175, 99-176
 100-177, 100-178
 101-179, 101-180
 102-181, 102-182
 103-183, 103-184
 104-185, 104-186
 105-187, 105-188
 106-189, 106-190
 107-191, 107-192
 108-193, 108-194
 109-195, 109-196
 110-197, 110-198
 111-199, 111-200
 112-201, 112-202
 113-203, 113-204
 114-205, 114-206
 115-207, 115-208
 116-209, 116-210
 117-211, 117-212
 118-213, 118-214
 119-215, 119-216
 120-217, 120-218
 121-219, 121-220
 122-221, 122-222
 123-223, 123-224
 124-225, 124-226
 125-227, 125-228
 126-229, 126-230
 127-231, 127-232
 128-233, 128-234
 129-235, 129-236
 130-237, 130-238
 131-239, 131-240
 132-241, 132-242
 133-243, 133-244
 134-245, 134-246
 135-247, 135-248
 136-249, 136-250
 137-251, 137-252
 138-253, 138-254
 139-255, 139-256
 140-257, 140-258
 141-259, 141-260
 142-261, 142-262
 143-263, 143-264
 144-265, 144-266
 145-267, 145-268
 146-269, 146-270
 147-271, 147-272
 148-273, 148-274
 149-275, 149-276
 150-277, 150-278
 151-279, 151-280
 152-281, 152-282
 153-283, 153-284
 154-285, 154-286
 155-287, 155-288
 156-289, 156-290
 157-291, 157-292
 158-293, 158-294
 159-295, 159-296
 160-297, 160-298
 161-299, 161-300
 162-301, 162-302
 163-303, 163-304
 164-305, 164-306
 165-307, 165-308
 166-309, 166-310
 167-311, 167-312
 168-313, 168-314
 169-315, 169-316
 170-317, 170-318
 171-319, 171-320
 172-321, 172-322
 173-323, 173-324
 174-325, 174-326
 175-327, 175-328
 176-329, 176-330
 177-331, 177-332
 178-333, 178-334
 179-335, 179-336
 180-337, 180-338
 181-339, 181-340
 182-341, 182-342
 183-343, 183-344
 184-345, 184-346
 185-347, 185-348
 186-349, 186-350
 187-351, 187-352
 188-353, 188-354
 189-355, 189-356
 190-357, 190-358
 191-359, 191-360
 192-361, 192-362
 193-363, 193-364
 194-365, 194-366
 195-367, 195-368
 196-369, 196-370
 197-371, 197-372
 198-373, 198-374
 199-375, 199-376
 200-377, 200-378
 201-379, 201-380
 202-381, 202-382
 203-383, 203-384
 204-385, 204-386
 205-387, 205-388
 206-389, 206-390
 207-391, 207-392
 208-393, 208-394
 209-395, 209-396
 210-397, 210-398
 211-399, 211-400
 212-401, 212-402
 213-403, 213-404
 214-405, 214-406
 215-407, 215-408
 216-409, 216-410
 217-411, 217-412
 218-413, 218-414
 219-415, 219-416
 220-417, 220-418
 221-419, 221-420
 222-421, 222-422
 223-423, 223-424
 224-425, 224-426
 225-427, 225-428
 226-429, 226-430
 227-431, 227-432

- SECRET**

- method

- 5 thermally spray-forming material selected from the group of materials consisting of metals, metal alloys, polymers, ceramics, and cermets onto a mandrel to form the tube stock; and

- removing the tube stock from the mandrel after it is formed.

4. The method of claim 3, wherein the tube stock is removed from the mandrel by melting the mandrel.

5. The method of claim 3, wherein the tube stock is removed from the mandrel by cooling the mandrel to decrease the mandrel diameter.

6. The method of claim 3, wherein the tube stock is removed from the mandrel by heating the tube stock to increase the diameter of the tube stock.

7. The method of claim 3, wherein the tube stock is removed from the mandrel by heating the tube stock to increase the diameter of the tube and cooling the mandrel to decrease the mandrel diameter.

8. The method of claim 3, wherein the tube stock is removed from the mandrel by the process of cross-rolling.

9. The method of claim 3, wherein the tube stock slides off the mandrel.

10. The method of claim 3, wherein before the tube stock is removed from the mandrel the tube stock is swaged in order to develop appropriate mechanical properties.

11. The method of claim 3, wherein before the tube stock is removed from the mandrel the tube stock is subjected to high mechanical pressure to develop appropriate mechanical properties.

12. The method of claim 3, wherein before or after the tube stock is removed from the mandrel the tube stock is placed in a traveling ring furnace for tempering and hardening.

13. The method of claim 3, wherein before or after the tube stock is removed from the mandrel the outer diameter of the tube stock is machined to a predetermined size.

14. The method of claim 3, wherein after the tube stock is removed from the mandrel the inner diameter of the tube stock is bored.

15. The method of claim 3, wherein after the tube stock is removed from the mandrel the inner diameter of the tube stock is reamed.

16. The method of claim 3, wherein before or after the tube stock is removed from the mandrel the tube stock is machined.

17. The method of claim 3, wherein before or after the tube stock is removed from the mandrel the tube stock is ground.

18. The method of claim 3, wherein after the tube stock is removed from the mandrel the tube stock is drawn.

19. A tube stock, comprising:
a tubular shell having an annular wall the thickness of which being at least eight grains and the average diameter of the grains being less than 64 microns.

20. The tube stock of claim 19, wherein the tubular shell is processed to form a medical device taken from the group of devices including stents, guide wires, catheters, markers, and lead tips.

21. A wire, comprising:
an elongated wire formed of grains and having a diameter of at least nine grains where the average diameter of the grains is less than 64 microns.

22. The wire of claim 21, wherein the wire is processed to form a medical device taken from the group of devices including stents, guide wires, catheters, markers, and lead tips.

23. A method of manufacturing tube stock through cold spray thermal processing, comprising:

introducing particles of a powder of at least one first material selected from the group consisting of metals, metal alloys, and polymers, with the particle size
5 ranging from about 1 to 64 microns, into a gas selected from the group consisting of Nitrogen (N₂), Oxygen (O₂), Air, Helium (He), Argon (Ar), Xenon (Xe), and Carbon Dioxide (CO₂);

introducing the gas and particles into a supersonic nozzle with an inlet
temperature between 380 to 420° Celsius, at an inlet velocity from about 300 to about
10 1,200 m/sec, and an inlet pressure of 1.5 to 2.5 Mpa to form a high-pressure stream;

directing the high pressure stream onto a mandrel, the distance between the nozzle and the mandrel being approximately 8 to 10 mm, and coating the mandrel with the particles to form the tube stock; and

removing the tube stock from the mandrel after it is formed.

24. A coated intravascular stent, the coating comprising:
a metallic coating material formed of grains where the average grain size
is less than 64 microns.

✓ ~~25.~~ A method of coating a medical device, comprising:
thermally spray-forming material onto the medical device to form the
coating where the type of thermal spray processing is selected from the group
consisting of cold spray, combustion, hvof, arc, and plasma and where the material
5 forming the coating is selected from the group consisting of metals, metal alloys,
polymers, ceramics, and cermets.

✓ 26. The method of claim 25, wherein the thickness of the coating is varied
on the medical device.

27. The method of claim 25, wherein the thickness of the coating is varied
along a length of the medical device.

28. The method of claim 25, wherein metallic alloys are sprayed onto the
medical device to form the coating.

29. The method of claim 25, wherein ceramic materials are sprayed onto the
medical device to form the coating.

30. The method of claim 25, wherein composites are coated onto the medical device.

31. The method of claim 25, wherein polymers are coated onto the medical device.

32. The method of claim 25, wherein a metallic coating is heated and grains are grown after the coating is sprayed onto the medical device.

33. The method of claim 25, wherein the medical device is swaged after coating.

34. The method of claim 25, wherein the medical device is drawn after coating.

35. The method of claim 34, wherein the medical device is annealed after being coated.

36. The method of claim 25, wherein the medical device is heated for post-processing after being coated.

37. The method of claim 25, wherein after coating, the medical device is cross-link processed.

38. The method of claim 25, wherein after coating, the medical device is post processed in a traveling ring furnace where the material is melted and re-solidified as the ring travels the length of the medical device.

39. The method of claim 25, wherein after coating the medical device is processed under high mechanical pressure in a vacuum to sinter grains of the medical device together.

40. The method of claim 25, wherein after coating an outer diameter of the medical device is post processed through centerless grinding.

41. The method of claim 25, wherein after coating an outer diameter of the medical device is post processed by drawing to reduce the coating thickness.

42. The method of claim 25, wherein after coating an inner diameter of the medical device is post processed by boring for improving both dimension and surface roughness.

43. A method of coating an intravascular stent through cold spray thermal processing, comprising:

introducing particles of a powder of at least one first material selected from the group consisting of metals, metal alloys, and polymers with a particle size
5 from about 1 to 64 microns, into a gas selected from the group consisting of Nitrogen

(N₂), Oxygen (O₂), Air, Helium (He), Argon (Ar), Xenon (Xe), or Carbon Dioxide (CO₂);

introducing the gas and particles into a supersonic nozzle with an inlet temperature between 380 to 420° Celsius, at an inlet velocity from about 300 to about
5 1,200 m/sec, and an inlet pressure of 1.5 to 2.5 Mpa to form a high pressure stream;

directing the high pressure stream at a stent placed on a mandrel 8 to 10 mm away from the nozzle, the stent formed from a second material selected from the group consisting of a metal, an alloy and a polymer, and coating the stent with the particles to form a coated stent; and

10 removing the coated stent from the mandrel.

ADD A1
ADD B1